



Product reference	Product number	COLOR		I [mA]	W		λ	K	
DRAGONeye®									
DE1-W3-854	4008321909725	white	1	350	1.1	15	5400	–	
DE1-W3-733	4008321909718	warm white	1	350	1.1	15	3300	–	
DE1-A2	4008321909732	red	1	350	0.8	18	617	–	
DE1-Y2	4008321909756	yellow	1	350	0.8	18	587	–	
DE1-T2	4008321909763	green	1	350	1.1	15	528	–	
DE1-B2	4008321909749	blue	1	350	1.1	15	465	–	

Other data (valid for all types):
 Photometric data: current values as per data sheet
 Operating temperature: –30 to +65 °C at the Tc point

DRAGONeye®

DRAGONeye® is an IP65 compact mini light with 1 high-flux Golden DRAGON® LED. The metal package ensures optimum heat removal. DRAGONeye® is ideal as a small luminaire head in single-LED luminaires or as part of an accent lighting, orientation lighting or route lighting system.

Technical characteristics

- Basic dimensions of DRAGONeye® H: 25 mm, Ø: 22 mm
- Integrated M10 thread for simple installation
- Two-core connecting cable 200 mm with open cable ends
- For backlighting and orientation lighting
- Type of protection IP65 to DIN EN 60529
- Metallic package for optimum heat removal
- Narrow beam angle for use as a spot source
- The modules can only be connected in series

