



| Product reference | Product number | W | V/Hz | | |
|--|----------------|----|-------------------|-----|------------------------------------|
| OSRAM DULUX® EL LONGLIFE E27 | | | | | |
| DULUX EL LL 5 W/827 E27 | 4050300357430 | 5 | 220...240/50...60 | 40 | LUMILUX Warm White |
| DULUX EL LL 7 W/827 E27 | 4050300288819 | 7 | 220...240/50...60 | 55 | LUMILUX Warm White ¹⁾ |
| DULUX EL LL 11 W/827 E27 ⁴⁾ | 4050300811598 | 11 | 220...240/50...60 | 90 | LUMILUX Warm White ¹⁾²⁾ |
| DULUX EL LL 15 W/827 E27 ⁴⁾ | 4050300811635 | 15 | 220...240/50...60 | 120 | LUMILUX Warm White ¹⁾²⁾ |
| DULUX EL LL 20 W/827 E27 | 4050300811673 | 20 | 220...240/50...60 | 160 | LUMILUX Warm White ¹⁾²⁾ |
| DULUX EL LL 23 W/827 E27 | 4050300028965 | 23 | 220...240/50...60 | 185 | LUMILUX Warm White ¹⁾²⁾ |
| DULUX EL LL 30 W/827 E27 | 4050300856827 | 30 | 220...240/50...60 | 160 | LUMILUX Warm White ¹⁾²⁾ |

| Product reference | Ra | Im | | d [mm] | l [mm] | | No. | |
|--|-----|------|-----|--------|---------|-----|-----|----|
| DULUX EL LL 5 W/827 E27 | 1 B | 240 | E27 | 36 | 113 ± 3 | 42 | 1 | 10 |
| DULUX EL LL 7 W/827 E27 | 1 B | 400 | E27 | 36 | 113 ± 3 | 42 | 1 | 10 |
| DULUX EL LL 11 W/827 E27 ⁴⁾ | 1 B | 660 | E27 | 45 | 117 ± 3 | 62 | 2 | 10 |
| DULUX EL LL 15 W/827 E27 ⁴⁾ | 1 B | 900 | E27 | 45 | 128 ± 3 | 65 | 2 | 10 |
| DULUX EL LL 20 W/827 E27 | 1 B | 1230 | E27 | 45 | 145 ± 3 | 73 | 2 | 10 |
| DULUX EL LL 23 W/827 E27 | 1 B | 1500 | E27 | 58 | 173 ± 3 | 100 | 2 | 10 |
| DULUX EL LL 30 W/827 E27 | 1 B | 1900 | E27 | 58 | 180 ± 3 | 165 | 3 | 10 |

OSRAM DULUX® EL LONGLIFE lamps with B22d base available on request.
OSRAM DULUX® EL LONGLIFE lamps are not suitable for use with dimmers or electronic switches.
Use outdoors only in enclosed and ventilated luminaires.

NEW
NEW

NEW
NEW

15000 h
500,000 + 100,000
E27

These compact fluorescent lamps offer high luminous efficacy with up to 80% savings in electricity costs. The E27 base means they can be easily fitted instead of ordinary light bulbs. These lamps also have excellent colour rendering and excellent light distribution.

- Extremely compact dimensions.
- Average life is 15,000 hours, corresponding to around 15 years at about 2.7 hours per day.
- Universal burning position.
- Low weight.
- Flicker-free starting and flicker-free operation.
- Reliable starting down to -30 °C (30 W down to -10 °C).
- More light without temperature problems in luminaires designed for ordinary light bulbs.
- OSRAM DULUX® EL 15 W and 20 W lamps are also available in 110 to 130 V versions (some of the technical data is different).

Commercial applications:

Restaurants, hotels, foyers, ticket offices, corridors, doctors' surgeries and offices.
Major advantage: much longer relamping intervals; meets the highest demands in terms of frequent on/off switching.

Domestic applications:

All rooms, especially where the lamps need to last a long time or have to withstand frequent on/off switching (500,000 switching operations³⁾).



OSRAM DULUX® EL LONGLIFE lamps are ideal for constant economical lighting.