




Product reference	Product number	W		Ra	Im CCG	TUBE d [mm]	l [mm]	No.		
<b>LUMILUX® T8, G13 base</b>										
L 10 W/827	4050300446165	10	LUMILUX Daylight	80...89	650	26	470	1	25	
L 15 W/865	4050300446189	15	LUMILUX Cool Daylight	80...89	900	26	438	1	25	
L 15 W/840	4050300446004	15	LUMILUX Cool White	80...89	950	26	438	1	25	
L 15 W/830	4050300446028	15	LUMILUX Warm White	80...89	950	26	438	1	25	
L 15 W/827	4050300446042	15	LUMILUX INTERNA	80...89	950	26	438	1	25	
L 16 W/840	4050300446066	16	LUMILUX Cool White	80...89	1250	26	720	1	25	
L 16 W/827	4050300446080	16	LUMILUX INTERNA	80...89	1250	26	720	1	25	
L 18 W/880	4008321027962	18	LUMILUX SKYWHITE	80...89	1300	26	590	1	25	
L 18 W/865	4050300517773	18	LUMILUX Cool Daylight	80...89	1300	26	590	1	25	
L 18 W/840 <sup>1)</sup>	4050300517797	18	LUMILUX Cool White	80...89	1350	26	590	1	25	
L 18 W/835	4050300447964	18	LUMILUX White	80...89	1350	26	590	1	25	
L 18 W/830	4050300517810	18	LUMILUX Warm White	80...89	1350	26	590	1	25	
L 18 W/827 <sup>1)</sup>	4050300517834	18	LUMILUX INTERNA	80...89	1350	26	590	1	25	
L 23 W/840	4050300446240	23	LUMILUX Cool White	80...89	1900	26	970	1	25	
L 23 W/830	4050300446264	23	LUMILUX Warm White	80...89	1900	26	970	1	25	
L 30 W/880	4008321027986	30	LUMILUX SKYWHITE	80...89	2350	26	895	1	25	
L 30 W/865	4050300518015	30	LUMILUX Cool Daylight	80...89	2350	26	895	1	25	
L 30 W/840	4050300518039	30	LUMILUX Cool White	80...89	2400	26	895	1	25	
L 30 W/830	4050300518053	30	LUMILUX Warm White	80...89	2400	26	895	1	25	
L 30 W/827	4050300518077	30	LUMILUX INTERNA	80...89	2400	26	895	1	25	
L 36 W/880	4008321002976	36	LUMILUX SKYWHITE	80...89	2900	26	1200	1	25	
L 36 W/865	4050300517858	36	LUMILUX Cool Daylight	80...89	3250	26	1200	1	25	
L 36 W/840-1	4050300518091	36	LUMILUX Cool White	80...89	3100	26	970	1	25	
L 36 W/840 <sup>1)</sup>	4050300517872	36	LUMILUX Cool White	80...89	3350	26	1200	1	25	
L 36 W/835	4050300447988	36	LUMILUX White	80...89	3350	26	1200	1	25	
L 36 W/830 <sup>1)</sup>	4050300517896	36	LUMILUX Warm White	80...89	3350	26	1200	1	25	
L 36 W/827-1	4050300518114	36	LUMILUX INTERNA	80...89	3100	26	970	1	25	
L 36 W/827 <sup>1)</sup>	4050300517919	36	LUMILUX INTERNA	80...89	3350	26	1200	1	25	
L 38 W/880	4008321072245	38	LUMILUX SKYWHITE	80...89	2950	26	1047	1	25	
L 38 W/840	4050300518138	38	LUMILUX Cool White	80...89	3300	26	1047	1	25	
L 38 W/830	4050300518152	38	LUMILUX Warm White	80...89	3300	26	1047	1	25	
L 58 W/880	4008321002990	54	LUMILUX SKYWHITE	80...89	4900	26	1500	1	25	
L 58 W/865	4050300517933	58	LUMILUX Cool Daylight	80...89	5000	26	1500	1	25	
L 58 W/840 <sup>1)</sup>	4050300517957	58	LUMILUX Cool White	80...89	5200	26	1500	1	25	
L 58 W/835	4050300448008	58	LUMILUX White	80...89	5200	26	1500	1	25	
L 58 W/830 <sup>1)</sup>	4050300517971	58	LUMILUX Warm White	80...89	5200	26	1500	1	25	
L 58 W/827 <sup>1)</sup>	4050300603049	58	LUMILUX INTERNA	80...89	5200	26	1500	1	25	

For QUICKTRONIC® electronic control gear see Section 11

Fluorescent lamps in LUMILUX® and BASIC light colours offer up to 10% energy savings compared with previous fluorescent lamps with a 38 mm tube diameter. They are designed to operate with conventional control gear and starters or with

QUICKTRONIC® electronic control gear. If used in starter circuits, these lamps can operate with standard control gear and recommended compensation capacitors.

1) Also available in industrial packs (... IVP) for bulk orders. Contains 30 lamps