









Product reference	Product number	W	lm		 d [mm]	 l max. [mm]	 LCL a [mm]	 No.		
POWERSTAR® HQI®-T										
HQI-T 250/D	40503000 15293	250	20000	E40	46	225	150	1	12	
HQI-BT 400/D ¹⁾	4050300 468471	400	35000	E40	62	285	175	2	12	
HQI-T 400/N ¹⁾	4050300 324647	400	42000	E40	46	273	175	1	12	
POWERSTAR® HQI®-T, coloured										
HQI-T 400 BLUE ²⁾	4050300 258300	360	–	E40	46	275	175	1	12	
HQI-T 400 GREEN ²⁾	4050300 258287	360	–	E40	46	275	175	1	12	
HQI-T 400 MAGENTA ²⁾	4050300 649535	440	–	E40	46	275	175	1	12	

POWERSTAR® HQI®-T with medium output and E40 screw base. Approved for use in enclosed luminaires.

Applications

- Industry
- Large halls

Benefits

- Output of up to 400 W
- Different light colours
- Also available in BLUE, GREEN and MAGENTA
- UV FILTER technology (see 5.04)

1) Operate with NAV® control gear. If operated with HQI® control gear see "Technical data" from page 5.37
2) Lamps with virtually monochromatic light